


ACCESSORIES

SUCTION AND FILTER UNIT



TAMPOPRINT

Suitable for the extraction of not inflammable gases

Suitable for the extraction of not inflammable dust particles

Triple acting filter unit, sound-proof

Contamination-free change of filter inserts

ORIGINAL

TAMPOPRINT

Tampon printing machines
ALFALAS® Laser systems
Automations
DMD® Industry Inkjet Printing Systems

SUCTION AND FILTER UNIT

Application area:

- has been developed especially for aerosols, ozone and dust particles.
- It can be used in recirculating air operation for tampon printing machines and laser lines.
- The unit is also equipped with a total operating hours counter, and it can be integrated into automations and printing lines or operated as a stand-alone unit.

Technical data Art.No.: 41 00 42

Suction power:	240 m ³ /h
Supppressure:	21 000 Pascal
Pre-filter:	F 5
Main filter:	Suspended matter filter H13
Activated carbon filter:	approx. 5 kg filling weight
Separation rate:	99,99%
Connecting sleeve:	2 x NW 45
Connection hose:	1x NW 45 with connecting sleeve, 1,5 mtr.
Noise level:	< 67 dB (A)
Drive:	Turbine B (continuous run)
Frequency:	50/60 Hz
Connected load:	1,2 kw
Mains voltage:	1/N/PE, 230 V
Weight:	45 kg
Length:	540 mm
Width:	380 mm
Height::	820 mm

Spare parts

Activated carbon filter	Art.No.: 41 01 58
Particle filter	Art.No.: 41 01 57
Pre-filter	Art.No.: 41 02 13

Description:

This compact unit is made of lacquered sheet steel and equipped with very powerful, maintenance-free suction components as well as triple acting filters. Because of the separate guiding of the extraction air it is not possible for the filtered air to be in any contact with electrical parts of the turbine.

Infinitely variable regulation of the suction power (from 0 - 100 %) is possible via a built in speed regulator.

Change of filters is easy and the filter inserts can be removed without contamination.

During operation the noise level of the suction and filter unit is less than 67 dB (A). Hence it works very quiet.

Attention:

Since the equipment is not explosion proof, it should NOT be used for extracting inflammable gases.

Explosion-proof units can be supplied on request.



TAMPOPRINT AG*

Lingwiesenstraße 1 · D-70825 Korntal-Münchingen
Phone: +49 7150 928-0 · Fax: +49 7150 928-400
E-Mail: info@tampoprint.de · www.tampoprint.de

TAMPOPRINT® INTERNATIONAL CORP.

Corporate Headquarters USA
1400 - 26th street, Vero Beach, Florida 32960
Phone : +1 772 778-8896, +1 800 810-8896
Fax: +1 772 778-8289
E-Mail: sales@tampoprint.com · www.tampoprint.com

TAMPOPRINT® S.A.R.L.

13, allée de Provence, B.P. 29
F-38295 Saint Quentin Fallavier Cédex
Phone : +33 474 9552-85 · Fax: +33 474 9552-61
E-Mail: info@tampoprint.fr · www.tampoprint.fr

TAMPOPRINT® Iberia S.A.U.

c/Caspe 127-135 local B · E-08013 Barcelona
Tel.: +34 93 2327161 · Fax: +34 93 2471500
E-Mail: tampoprint@tampoprint.es · www.tampoprint.es

ORIGINAL

TAMPOPRINT®

The reproduction of trademarks and brands used in this brochure, even if not explicitly expressed, does not justify the assumption that such names or symbols may be considered as free as defined by the trademark law and may therefore freely be used by anybody. The rights are property of the respective owner.

TAMPOPRINT products are permanently updated to keep pace with the latest technological developments. For this reason, figures and descriptions are non-binding.

Subject to alterations!